

# Using Technology to Improve Safety within High Output:

## *Safe & Efficient Access*

David M Underwood

Director of Engineering, Design & Improvement

# Introduction


- Network Rail High Output Fleet:
  - 2 Track Relaying Systems (TRS)
  - 5 Ballast Cleaning Systems (BCS)
- Deploy 5 nights/week, with adjacent lines open and typically handing back at 100mph.
- Delivering 70% of plain line linear volume in Great Britain in CP5 (Apr 2014 – Mar 2019).



# Offices & Depots

5 Depots

2 Central Offices



**High Output**  
Track Renewals

## Operations Bases HOOB locations



**High Output**  
Track Renewals

# ***Blocking the Line: The Need to Change....***


# Current Protection Methods for Line Blockages

Handbook 8 of the rule book describes the process for taking a Line Blockage:

1. The signaller arranges for a protecting signal to be placed to danger
2. Signaller installs reminder appliance on the panel.

If safety of the line is affected then a form of additional protection is required:

- a) Signal disconnection
- b) Detonators and Possession Limit Board (PLB)
- c) Installation of a Track Circuit Operating Device (TCOD)



# Problems with the Current Arrangements

- Protection methods require staff to be lineside.
- Complicated and relies on multiple 1 to 1 verbal communications
- Many parties all with different roles and responsibilities
- The method that tends to be the preferred option is PLB's and detonators. The activity is:
  - Potentially hazardous requiring staff to enter the 4' every time.
  - Slow and time consuming utilising valuable working time

# Safety Stats – Operational Close Calls

- RAIL INDUSTRY 2017-18 YTD - 157 operational close call incidents relating to Line blockages.
- *Protection incorrectly placed*
- *Miscommunication between COSS and Signaller*
- *Miscommunication between COSS and Possession support staff*
- *Signaller error*



# ***The High Output Safe & Efficient Access Project***

# ***Aims of the Safe & Efficient Access Project***

- To create a step change improvement in safety by removing staff from the 4 foot when placing and removing protection.
- To reduce the amount of time taken to take and handback blockages of the line (possessions and line blockages)



## Network Rail Safety Vision

*Outstanding safety performance and outstanding business performance go hand in hand*

# Line Blockages within High Output

- High Output activities require line blockages of the adjacent line varying from 5-15 minutes per night.
  - 12 x Line blockages for TRS
  - 6 x Line blockages for BCS
- All of which affect safety of the line and require a form of additional protection.



**The preferred method of additional protection for High Output has been detonator protection.**

# Recent Success in High Output

## Introduction of ZKL3000 (RC)

Sponsored through Product acceptance by High Output



Approval and Authorisation			
Date	Print Name	Signature	Position
16/05/2017	David Underwood	<i>[Signature]</i>	Programme Engineering Manager
16/05/2017	John McKee	<i>[Signature]</i>	S&T Engineer

History Record		
Revision	Date	Amendment
1.0		Initial Issue
2.0	31 <sup>st</sup> March 2016	Post ACJV Transition into Network Rail review and update
2.1	May 2017	Amended/updated

IP 5195 - ZKL 3000 Utilisation May 2017 final  
Rev 2.1


Page 1 of 10  
Date: May 2017




Certificate of Acceptance	
Manufacturer: Dual Inertive	Model: ZKL 3000 (RC)
Product Description: A portable, computerised PCEC for setting track circuits, setting portable engineering operations and providing a visual display of the status of the track circuit.	Product Image:
Scope of Acceptance: This certificate is issued for the use of the ZKL 3000 (RC) on the following track circuits: [List of track circuits]	Signature: <i>[Signature]</i>
Specific Conditions: The following conditions are specific to the approved product covered within this Certificate. These conditions must be adhered to in order to ensure full compliance with the conditions specified in this certificate.	Signature: <i>[Signature]</i>

# The difference to TRS since Introducing ZKL

## PLB & Detonators



## ZKL3000 (RC)



Day	Line Blocks Req	Using PLB and Detonators as additional Protection			Using ZKL3000 (RC) as additional Protection		
		Visits to the 4 foot	No. of Phone calls	Average time taken to place and remove protection	Visits to the 4 foot	No. of Phone calls	Average time taken to place and remove protection
M	12	24 (2 per line block)	96 (8 per line block)	24 minutes	1 (install)	24	4 min
T	12	24	96	24 minutes	0	24	4 min
W	12	24	96	24 minutes	0	24	4 min
T	12	24	96	24 minutes	0	24	4 min
F	12	24	96	24 minutes	1 (remove)	24	4 min
<b>Total</b>	<b>60</b>	<b>120</b>	<b>480</b>	<b>2 hours</b>	<b>2</b>	<b>120</b>	<b>24 mins</b>

# The Logic – ZKL Vs Conventional



Protection Type	Visits to the 4 foot (for 1 line blockage)	Communication (for 1 line blockage)	Time (for 1 line blockage)
PLB & Dets	1 to take 1 to handback 2 total	4 calls to take 4 calls to handback 8 total	2 mins to deploy and remove
ZKL3000 (RC)	installed once prior to shift	1 call to take 1 call to handback 2 total	20 seconds to deploy and remove

## TRS

- **4 foot visits = reduced by 118 (97%) per week**
- **Phone Calls = reduced by 360 (75%) per week**
- **Protection time = reduced by 1 hour 36 mins per week**

## BCS

- **4 foot visits = reduced by 58 (97%) per week**
- **Phone Calls = reduced by 180 (75%) per week**
- **Protection time = reduced by 48mins (80%) per week**



# Summary

- Reduced the risk of exposing staff to moving trains when placing / removing protection for line blockages.
- Reduced line blockage visits to the 4 foot by 97% per week per system
- Reduced the amount of phone calls for line blockages by 75% per week per system
- Gained additional 96minutes (TRS) and 48 mins (BCS) per week per system through introduction of ZKL3000 (RC)



# The future for High Output and Network Rail

- Incab Flexible Train Arrival Point (FTAP)
- ZKL3000(RC) mobile app
- ZKL's installed at fixed locations
- Tamping using ZKL3000 as protection
- High Output Protection Zone
- Personal Warning System (PWS)
- Wireless train warning system (SATWS, ATWS)
- Remote TSR Boards





# *Thank you*

For further information contact:

Neil Sunner

Project Manager (High Output Improvement)

Email: [neil.sunner@networkrail.co.uk](mailto:neil.sunner@networkrail.co.uk)

Phone: 07834147559